

PRODUCT INFORMATION

HEAT STAKING MACHINE B7812 BHS HOT AIR®



- > Two-step Hot Air Riveting Technology
- > High output on small footprint
- > Quick-exchange tooling modules for multiple product production
- > Highest rivet strength
- > Maximum process control
- > Alternative heating methods for reduced temperature impact on product

Fully-automatic heat staking machine for joining of thermoplastics

The fully-automatic heat staking machine is designed modularly and meets all typical requirements of the automotive (electronics) industry on process reproducibility, shortest possible cycle times, and flexibility.

Due to the separation of the process steps heating and forming into two process stations and the magnetic transportation system, the cycle time can be reduced to a minimum and is only depending on the heating time. A robot automatically picks up pre-assembled product from conveyor onto the magnetizing transportation system and after processing automatically back onto conveyor. The modular design and quick-exchangeable tooling allows to produce different products on the same machine. The special riveting tooling design ensures highest quality and strength of the rivet without flash throughout all tolerance-related pin volume differences.


Using a touch panel PC, the process can be programmed intuitively and quickly, and the actual values for each process step are displayed. Process, product and machine data are continuously monitored and can be passed on to a database for each component.

bdtronic 

DISPENSING
IMPREGNATION
PLASMA
HOT RIVETING

HEAT STAKING MACHINE B7812 BHS

BHS HOT AIR® PRINCIPLE



MODULAR EXTENSIONS

- > Up to 12 riveting pins per product
- > Pin detection before riveting via profile scanner
- > Rivet inspection after riveting via profile scanner
- > Traceability via MES communication
- > Additional tooling for other products

TECHNICAL DATA

Machine dimensions (WxDxH) / Weight	1200 x 1475 x 2200 mm / 1.400 kg
External Control Cabinet with cable bridge	Distance to machine max. 700 mm, approx. 1200 mm x 300 mm x 2200 mm
Max. product dimensions / weight	WPC size 240 x 240 mm / max. 500 gr
Working height	approx. 950 mm +/-50 mm
Access on rear side for tool exchange by folding doors	
Control	Beckhoff or OpCon PLUS
Operation	Touch panel, colored; bdtronic software visualization or OpCon PLUS
Electrical power supply	CEE plug 400 VAC 3P/N/PE, 50 Hz, 32 A
Pneumatic supply	min bei 5 bar,nominal diameter 7.2 mm
Linear transportation system with 6 movers for product nest	
Color	RAL 7035 (ESD)

SOFTWARE

- > Standard languages German and English
- > User management
- > Error management with clear text messages
- > Data logging of error messages
- > Maintenance function

(Errors and changes reserved, as of January 2019)

- > Service hotline (German/English/French)
- > Response service MO - FR
- > Spare parts service
- > Service and maintenance
- > Process and component optimization in in-house development centers
- > Trials and development in well equipped technical centers
- > Training for machine user, machine setter and maintenance personnel
- > Seminars for machines user, machine setter and maintenance personnel

bdtronic GmbH
Ahornweg 4
97990 Weikersheim

T +49 7934 104 - 0
F +49 7934 104 - 371
sales@bdtronic.de
www.bdtronic.de

bdtronic 

DISPENSING
IMPREGNATION
PLASMA
HOT RIVETING